



Streamlines production and guarantees fast finishing with consistent quality, cutting time and overhead.

Multi-substrate high-end slitter rewinder

With JUPITER you are 100% sure of the quality you deliver, encouraging customer loyalty in the most demanding circumstances.

Built to communicate with all workflow link brands, the rewinder runs at full speed and only stops for pre-defined defects to be removed or corrected.

With the exclusive Automatic Workflow Management System, what makes the difference is when the rewinder stops, any corrective action is entirely automatic and the end result is error-free, every time.

Only this way do converters achieve total reproducibility of the finished label by zeroing the risk of human error.

JUPITER handles multi-substrates from 12 to 450µm with 3 different rewinding tensions for unsupported film, SA labels and clear-on-clear labels.

JUPITER with Automatic Workflow Management System enables fully automatic correction procedures, leading to consistency and failsafe quality of the finished label.

TECHNICAL DATASHEET

	TC530	TCW630	TCW670	
Max. working width	530	630	670	mm
Max. speed	320	400	400	m/min
Max. unwinding diam.	800	1100	1100	m/min
Max. rewinder diam. on single shaft	600	800	800	mm
Max. rewinder diam. on dual shaft	420	750	750	mm
Min. slitting width with regular knives	15	30	30	mm
Slitting accuracy	+/- 0.15	+/- 0.15	+/- 0.15	mm
Min. side trim width	1.5	1.5	1.5	mm

Label type: SA paper and plastic labels, flexible packaging and unsupported paper.